

In-Wall Timer - Spring Wound Timer, No Hold, 15-Minute, White

Item SW15MWK



PRODUCT DESCRIPTION

The SW Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multigang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ► 15-Minute timer
- ► SPST (Single-Pole Single-Throw)
- ► Breaks circuit at end of timing cycle
- ► No electricity required to operate
- ► Replaces any standard or decorator single- or multi-gang wall switch
- ► Automatically limits ON time for energy consuming loads
- Quick and easy installation
- ► Time-saving up front terminal connection with teeter-type terminals
- ► Incandescent/fluorescent/CFL/LED compatible
- ► No neutral connection is required

TECHNICAL DATA

*7*2

SW15MWK
Spring Wound Timer, No Hold, 15-Minute, White
078275143470
Intermatic
TUNISIA
1-Year limited

Material Specifications

Includes Wall Plate No

Load	Ratings
------	---------

Resistive Heater	20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC
Tungsten (Incandescent) Range(s)	7 A, 125 VAC, 50/60 Hz, 875 W
Meter Load Detings Denge	1 IID 105 VAC. 0 IID 050 VAC

Motor Load Ratings Ranges 1 HP, 125 VAC; 2 HP, 250 VAC

Electrical Specifications

Input Voltage Range(s)	125-277 VAC, 50/60 Hz
Switch Type	SPST
Neutral Connection Required	No

Environmental Specifications

Temperature (operation) $40 - 120 \, ^{\circ}\text{F} \, / \, 4 - 49 \, ^{\circ}\text{C}$

Packaging	
Shipping Weight (lbs)	0.35
Unit Carton Dimensions (H x W x D) in	6.7 x 3 x 5 in



Standards and Certifications	
Other Certifications and Compatibilities	RU
California Proposition 65	DEHP