

# Weather Proof Cover - Extra-Duty Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, 4.75" Clear

PRODUCT DESCRIPTION

## Item WP5500C



# FEATURES

- Plastic In-Use Weatherproof Covers are extra-duty rated and easy to install. Covers come with a gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.
- ► Complies with 2020 NEC Article 406.9 (B)(1) for wet locations and extra-duty applications
- ► CEC Article 26-702 Compliant
- ► UL Certified for Type 3R outdoor enclosures
- ► Meets requirements for cold impact testing: -60° F (-51° C)
- ► Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts
- ▶ 1/8" (3 mm) thick, pre-adhered neoprene gasket with slits for mounting screws
- ► Lockable hasp: All models accept up to 1/4" (6 mm) dia. shank
- ▶ Impact rated: 12 lb. impact test to ensure cover remains intact
- ▶ Reinforced hinge pin designed to exceed 40 lb. hinge hang/stress test
- ► Warranty: 1-year limited

#### **APPLICATIONS**

► Receptacle Protection

### **TECHNICAL DATA**

General	
Model Number	WP5500C
Description	Extra-Duty Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, 4.75" Clear
UPC Code	078275145399
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications		
Number of Included Inserts	6	
Insert Types Included	WP107; WP213	
Hinge Direction	Vertical	
Is Extra-Duty Rated	Yes	

Dimensions	
Lockable Hasp Maximum Diameter (in)	1/4
Lockable Hasp Maximum Diameter (mm)	6
Product Dimensions (H x W x D) in	6 x 6.625 x 4.75 in
Accepted Cord Size Max	1x6 AWG
Box Type	Double

Material Specifications	
Color	Clear; Gray
Weatherproof Cover Material	UV Stabilized Plastic



Packaging	
Shipping Weight (lbs)	1.1
Unit Carton Dimensions (H x W x L) in	6.5 x 4 x 6.5 in

Standards and Certifications		
UL Certification	cULus	
California Proposition 65	None	
RoHS Certification	χ	



# **ACCESSORIES**



WP107

Double-Gang Round Insert, 1 3/8", 1 5/8", 1 3/4"



WP213 Double-Gang Round Insert, 2 1/8", 2 5/8"