

Occupancy Sensor - Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only

Item IOS-CMP-UMX



**NOM**

**PRODUCT DESCRIPTION**

The IOS-CMP-U 360° Passive Infrared (PIR) Line Voltage Occupancy Sensors control lighting systems based on occupancy and ambient light levels. When movement is detected, the sensor turns the lights ON. If no movement is detected for a user-specified time, the lights are turned OFF. The occupancy sensor provides a 360° coverage pattern, up to 1200 square feet.

**FEATURES**

- ▶ PIR technology sensing for presence detection
- ▶ Coverage: 1200 ft2 when mounted on 8 to 11 ft ceiling
- ▶ Zero-crossing technology for long life and performance
- ▶ Adjustable ambient light sensor override
- ▶ Requires neutral connection
- ▶ Incandescent/Fluorescent/CFL/LED compatible

**APPLICATIONS**

- ▶ Indoor Sensing Control

**TECHNICAL DATA**

General	
Model Number	IOS-CMP-UMX
Description	Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only
UPC Code	078275139916
Brand	Intermatic
Warranty Period	2-Year limited
Country of Origin (Intermatic)	CHINA
Control Specifications	
Sensor Switch Type	Occupancy
Sensor Technology	PIR (Passive Infrared)
Adjustable Time Delay Min	15 sec
Adjustable Time Delay Max	30 min
Adjustable Light Level Min	10 fc
Adjustable Light Level Max	150 fc
PIR Coverage Area (sq ft)	1200
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Mechanical Specifications	
Mount Type	Ceiling
PIR Coverage Pattern (degrees)	360
Maximum Mounting Height (ft)	8-11 ft
Dimensions	
Product Height (in)	1.375
Product Height (mm)	35
Product Diameter (in)	4.563

Product Diameter (mm)	116
-----------------------	-----

Material Specifications

Color	White
-------	-------

Load Ratings

Tungsten Range(s)	800 W, 120/125 VAC
Resistive Load Ratings Ranges	10 A, 120/125 VAC
Motor Load Ratings Ranges	1/4 HP, 120/125 VAC
Electronic Ballast Load Ratings Ranges	800 VA,120/125 VAC; 1600 VA, 277 VAC

Electrical Specifications

Input Voltage Range(s)	120/277 VAC, 60 Hz
Occupancy Sensor Power Type	Line Voltage
Neutral Connection Required	Yes

Packaging

Shipping Weight (lbs)	0.4
Shipping Weight (kg)	0.181
Unit Carton Dimensions (H x W x L) in	2 x 5 x 5 in

Environmental Specifications

Temperature (operation)	32 - 131°F / 0 - 55°C
-------------------------	-----------------------

Standards and Certifications

Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	X