

In-Wall Timer

- 24-Hour Heavy-Duty Mechanical In-Wall Timer, Timer and Toggle Switch, 120 VAC, 20A, SPST, 2 Gang, White

Item KM2ST-2G



PRODUCT DESCRIPTION

For installing on circuits up to 20 A, this timer provides automatic 24-hour ON/OFF control of outdoor/indoor lighting, fans, pumps, office equipment and other types of loads.

FEATURES

- ▶ 72 trippers provide 36 ON/OFF events per 24-hour period
- ▶ Captive trippers with 20-minute switching intervals
- ▶ 3-way (SPDT) switch available
- ▶ 3-position ON/OFF/AUTO override provides continuous ON or OFF operation
- ▶ Reliable synchronous timer motor
- ▶ Multiple wall plates available
- ▶ Easy wiring and installation
- ▶ Heavy-Duty 20 A rating
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	KM2ST-2G
Description	24-Hour Heavy-Duty Mechanical In-Wall Timer, Timer and Toggle Switch, 120 VAC, 20A, SPST, 2 Gang, White
UPC Code	078275153714
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Maximum ON/OFF Operations	36
Operation Mode	24 hour
Mechanism Type	Analog/Mechanical
Minimum ON/OFF Times	20 min
Application Compatibilities	Incandescent; Fluorescent; CFL
Mechanical Specifications	
Wall Plate Configurations	2-Gang
Material Specifications	
Color	White
Includes Wall Plate	Yes
Load Ratings	

Motor Load Ratings Ranges	1 HP, 120 VAC, 60 Hz
Incandescent Load Ratings (Multi-Gang)	1350 W, 120 VAC, 60 Hz
Incandescent Multi Gang Load Ratings Ranges	1350 W, 120 VAC, 60 Hz
Inductive Load Ratings Ranges	8 A, 120 VAC, 60 Hz

Electrical Specifications	
Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Switch Type	SPST
Neutral Connection Required	Yes
Wiring Option	SPST (3) #14 AWG color coded; SPDT (4) #14 AWG color coded

Environmental Specifications	
Operating Humidity	0 to 95%, Non-condensing
Temperature (operation)	-40 - 180 °F / -40 - 82 °C

Packaging	
Shipping Weight (lbs)	0.509
Unit Carton Dimensions (H x W x D) in	2.5 x 4.75 x 7.5 in

Standards and Certifications	
UL Certification	cULus
CSA Certification	cCSAus
California Proposition 65	DEHP
RoHS Certification	X

ACCESSORIES



24--00041
Wall Plate for KM2ST-2G, 2 Gang (Timer and Toggle Switch), White