

Weather Proof Cover - Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.75" Clear

Item WP1100C



PRODUCT DESCRIPTION

Plastic In-Use Weatherproof Covers are easy to install and include adhered gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

FEATURES

- ► Complies with 2020 NEC Article 314.15 for damp and wet locations
- ► UL Certified for Type 3R outdoor enclosures
- ► Meets requirements for cold impact testing: -60° F (-51° C)
- ► Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts
- ▶ 1/8" (3 mm) thick, pre-adhered neoprene gasket with slits for mounting screws
- Lockable hasp: All models accept up to 1/4" (6 mm) dia shank, except WP3100C & WP3103C accept up to 1/8" (3 mm) dia shank
- ► Three inserts provided with all models that allow each model to meet multiple installations (up to 16 configurations)
- ► Max cord size: (2) #14 AWG or (1) #12 AWG
- ► Mounts vertically or horizontally
- ► Warranty: 1-year limited

APPLICATIONS

► Receptacle Protection

TECHNICAL DATA

c(UL)us

General		
Model Number	WP1100C	
Description	Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.75" Clear	
UPC Code	078275072817	
Brand	Intermatic	
Country of Origin (Intermatic)	MEXICO	
Warranty Period	1-Year limited	

Mechanical Specifications	
Number of Included Inserts	3
Insert Types Included	WP17
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	No

Dimensions	
Lockable Hasp Maximum Diameter (in)	1/4
Lockable Hasp Maximum Diameter (mm)	6
Product Dimensions (H x W x D) in	5.75 x 4 x 2.75 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Box Type	Single

Material Specifications	
Color	Clear
Weatherproof Cover Material	UV Stabilized Plastic



Packaging	
Shipping Weight (lbs)	0.444
Unit Carton Dimensions (H x W x L) in	3.001 x 4.501 x 6.251 in

Standards and Certifications		
UL Certification	cULus	
California Proposition 65	None	
RoHS Certification	X	



ACCESSORIES



WP17 Single-Gang Inserts (3)