

Occupancy Sensor - Commercial Grade Dual Load In-Wall PIR Occupancy/Vacancy Sensor, No Neutral Required, White, Mexico Sales Only

Item IOS-DDR-WHMX



PRODUCT DESCRIPTION

The passive infrared sensors work by detecting the difference between heat emitted from the human body in motion and the background space. The sensor switch can turn a load ON and hold it as long as the sensor detects occupancy. After no motion is detected for the set time delay, the load turns OFF automatically. The IOS-DDR has two relays (equal to Dual Load Switch).

FEATURES

- ▶ Passive Infrared (PIR) sensing for presence detection
- ▶ Coverage: 180°, 1200 ft2 with non-obstructed views
- ▶ Independent load control for each circuit
- ▶ Zero-crossing technology for long life and performance
- ▶ Incandescent/Fluorescent/CFL/LED compatible
- ▶ IOS-DDR-WH does NOT require a neutral
- ▶ Fits standard decorator wall plate (included)
- ▶ Time delay OFF ranging from 15 seconds to 30 minutes
- ▶ Two ON/OFF push buttons allow control of two loads independently
- ▶ Multiple configurations (e.g. auto ON-manual ON, auto ON-auto ON) for primary and secondary loads

APPLICATIONS

- ▶ Indoor Sensing Control

TECHNICAL DATA

General	
Model Number	IOS-DDR-WHMX
Description	Commercial Grade Dual Load In-Wall PIR Occupancy/Vacancy Sensor, No Neutral Required, White, Mexico Sales Only
UPC Code	078275125568
Brand	Intermatic
Warranty Period	5-Year limited
Country of Origin (Intermatic)	CHINA
Control Specifications	
Sensor Switch Type	Occupancy; Vacancy
Sensor Technology	PIR (Passive Infrared)
Adjustable Time Delay Min	15 sec
Adjustable Time Delay Max	30 min
Adjustable Light Level Min	30 lux
Adjustable Light Level Max	Daylight
Has Walk-Through Detection	Yes
PIR Coverage Area (sq ft)	1200
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Mechanical Specifications	
Mount Type	In-Wall
PIR Coverage Pattern (degrees)	180
Maximum Mounting Height (ft)	4 ft

Dimensions		
Product Height (in)		2.625
Product Height (mm)		67
Product Width (in)		1.3125
Product Width (mm)		33
Product Depth (in)		1.75
Product Depth (mm)		44
Material Specifications		
Color		White
Includes Wall Plate		Yes
Load Ratings		
Tungsten Range(s)		800 W, 120/125 VAC
Resistive Load Ratings Ranges		10 A, 120/125 VAC
Motor Load Ratings Ranges		1/4 HP, 120/125 VAC
Electronic Ballast Load Ratings Ranges		800 VA,120/125 VAC; 1600 VA, 277 VAC
Electrical Specifications		
Input Voltage Range(s)		120/125 VAC, 60 Hz
Occupancy Sensor Power Type		Line Voltage
Number of Circuits		2
Packaging		
Shipping Weight (lbs)		0.399
Shipping Weight (kg)		0.181
Unit Carton Dimensions (H x W x L) in		5 x 2.25 x 3 in
Environmental Specifications		
Temperature (operation)		32 - 131°F / 0 - 55°C
Standards and Certifications		
Other Certifications and Compatibilities		NOM
California Proposition 65		None
RoHS Certification		X