

**In-Wall Timer** - 7-Day Standard Programmable Timer, 125 VAC, 15A, White

Item EI500WC



**PRODUCT DESCRIPTION**

For installation on 15 A circuits, this timer provides 24-hour or 7-day programming of lights, fans, pumps and other medium-duty loads. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

**FEATURES**

- ▶ 7-day programmable schedules with 14 ON/OFF events
- ▶ Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- ▶ Single-pole circuit
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ Built-in rechargeable, non-serviceable battery backup
- ▶ Requires neutral connection
- ▶ Backlit LCD display
- ▶ Decorator switch plate not included

**APPLICATIONS**

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

**TECHNICAL DATA**

General	
Model Number	EI500WC
Description	7-Day Standard Programmable Timer, 125 VAC, 15A, White
UPC Code	078275105232
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Operations	14
Operation Mode	24 hour
Mechanism Type	Digital/Electrical
Backup Type	Battery
Battery Type	Nickel-metal hydride rechargeable battery
Battery Service Type	Non-Serviceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Chemical Composition of the Battery Cell	Oxyhydroxide; Alloy Powder
Number of Batteries Included	1
Battery Weight (grams)	3.5
Number of Lithium Metal Cells in Battery	N/A
Watt Hours Per Battery	0.096
Lithium Content (grams) in Battery	N/A

**Mechanical Specifications**

Wall Plate Configurations

Single-Gang

Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.438 in
-----------------------------------	-------------------------

Material Specifications

Color	White
-------	-------

Load Ratings

General Purpose	15 A, 125 VAC, 60 Hz
Resistive Heater	15 A, 1875 W
Tungsten (Incandescent) Range(s)	1000 W
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP, 125 VAC, 60 Hz
Inductive Load Ratings Ranges	1000 VA, 125 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Benefits

Number of Lithium-ion Cells in Battery	N/A
--	-----

Packaging

Shipping Weight (lbs)	0.472
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

Standards and Certifications

UL Certification	cULus
California Proposition 65	DEHP
RoHS Certification	X