

In-Wall Timer - 7-Day Standard Programmable Timer, 125 VAC, 15A, Light Almond

Item EI500LAC



PRODUCT DESCRIPTION

For installation on 15 A circuits, this timer provides 24-hour or 7-day programming of lights, fans, pumps and other medium-duty loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ 7-day programmable schedules with 14 ON/OFF events
- ▶ Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- ▶ Single-pole circuit
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ Built-in rechargeable, non-serviceable battery backup
- ▶ Requires neutral connection
- ▶ Backlit LCD display
- ▶ Decorator switch plate not included

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	EI500LAC
Description	7-Day Standard Programmable Timer, 125 VAC, 15A, Light Almond
UPC Code	078275105225
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Operations	14
Operation Mode	24 hour
Mechanism Type	Digital/Electrical
Backup Type	Battery
Battery Type	Nickel-metal hydride rechargeable battery
Battery Service Type	Non-Serviceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Chemical Composition of the Battery Cell	Oxyhydroxide; Alloy Powder
Number of Batteries Included	1
Battery Weight (grams)	3.5
Number of Lithium Metal Cells in Battery	N/A
Watt Hours Per Battery	0.096
Lithium Content (grams) in Battery	N/A
Mechanical Specifications	

Wall Plate Configurations

Single-Gang

Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.438 in
Material Specifications	
Color	Light Almond
Includes Wall Plate	No
Load Ratings	
General Purpose	15 A, 1875 W
Resistive Heater	15 A, 1875 W
Tungsten (Incandescent) Range(s)	1000 W
Ballast Fluorescent	8 A, 1000 VA
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP, 125 VAC, 60 Hz
Inductive Load Ratings Ranges	1000 VA, 125 VAC, 60 Hz
Electrical Specifications	
Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Environmental Specifications	
Temperature (operation)	32 - 104 °F / 0 - 40 °C
Benefits	
Number of Lithium-ion Cells in Battery	N/A
Packaging	
Shipping Weight (lbs)	0.351
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in
Standards and Certifications	
UL Certification	cULus
California Proposition 65	DEHP
RoHS Certification	X