

Photocontrol - Stem and Swivel Mount Thermal Photocontrol, 120 V, Mexico Sales Only

Item K4221CMX



PRODUCT DESCRIPTION

These photocontrols are provided with a swivel arm for easy and flexible installation to standard outdoor light fixtures or electrical boxes.

FEATURES

- ► Mechanical bimetal switch with Cadmium Sulfide photocell
- ► Delay feature prevents unwanted OFF switching
- ► High strength, UV resistant plastic housing
- ► Swivel with 1/2"-14 NPSM threaded stem
- ► Washer gasket and locking nut included
- ▶ #18 AWG, 6" wire leads

APPLICATIONS

► Outdoor Lighting Control

TECHNICAL DATA

| General | | |
|--------------------------------|--|--|
| Model Number | K4221CMX | |
| Description | Stem and Swivel Mount Thermal Photocontrol, 120 V, Mexico Sales Only | |
| UPC Code | 078275002029 | |
| Brand | Intermatic | |
| Country of Origin (Intermatic) | MEXICO | |
| Warranty Period | 2-Year limited | |

| Control Specifications | |
|------------------------------|--------------------------------|
| Sensor Time Delay | 30 sec to 90 sec |
| Photocell Type | Cadmium Sulfide |
| Photo Control Switch Type | Mechanical Bimetal |
| Fail Mode | ON |
| Activation On | 1 to 5 fc |
| Activation Off | 3 to 15 fc |
| Photocontrol Type | Thermal |
| Application Compatibilities | HID; Fluorescent; Incandescent |
| Photocontrol Style | Stem and Swivel Mount |
| Photocontrol Sensor Location | Side |

| Dimensions | | |
|-----------------------|--------|--|
| Product Height (in) | 5 | |
| Product Height (mm) | 139.7 | |
| Product Width (in) | 1.5625 | |
| Product Width (mm) | 39.7 | |
| Product Depth (in) | 1.5625 | |
| Product Depth (mm) | 39.7 | |
| Wire Lead Length (in) | 9 | |



Wire Lead Length (mm) 228.6

Gray

Wire Size Max #18 AWG

Material Specifications
Cover Color

Housing Material Polycarbonate

Load Ratings

Magnetic Ballast Range(s) 8.3 A, 1000 VA

Tungsten Range(s) 15 A, 1800 W

Electrical Specifications

Wiring Option Wire leads
Input Voltage Range(s) 120 VAC, 50/60 Hz

Packaging

Shipping Weight (lbs) 0.299

Unit Carton Dimensions (H x W x D) in 4.88 x 1.75 x 3 in

Operating Specifications

Expected Lifetime (Years) 5
Expected Lifetime (Operations) 3650

Environmental Specifications

Temperature (operation) -40°C..70°C

Usage Environments Outdoor

Standards and Certifications

UL Certification UL

CSA Certification cCSAus

Other Certifications and Compatibilities NOM; Title 20
California Proposition 65 None

RoHS Certification X



ACCESSORIES



22LG116

Light Guard Accessory for K4100 Series, K4200 Series Thermal Photocontrols



K42-SW-A

Swivel Arm Accessory for EK4136S, K4100 Series Stem Light Shield Accessory for EK4036S, EK4436SM, K4000 Mount Photocontrols



6LV1352

Series Button Photocontrols