

Photocontrol - Stem and Swivel Mount Thermal Photocontrol, 120-277 V, Mexico Sales Only

Item K4236CMX



PRODUCT DESCRIPTION

These photocontrols are provided with a swivel arm for easy and flexible installation to standard outdoor light fixtures or electrical boxes.

FEATURES

- ▶ Mechanical bimetal switch with Cadmium Sulfide photocell
- ▶ Delay feature prevents unwanted OFF switching
- ▶ High strength, UV resistant plastic housing
- ▶ Swivel with 1/2"-14 NPSM threaded stem
- ▶ Washer gasket and locking nut included
- ▶ #18 AWG, 6" wire leads

APPLICATIONS

- ▶ Outdoor Lighting Control

TECHNICAL DATA

| General | |
|--------------------------------|--|
| Model Number | K4236CMX |
| Description | Stem and Swivel Mount Thermal Photocontrol, 120-277 V, Mexico Sales Only |
| UPC Code | 078275029606 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 2-Year limited |
| Control Specifications | |
| Activation On | 1.5 fc |
| Activation Off | 3 to 15 fc |
| Photocontrol Type | Thermal |
| Application Compatibilities | Fluorescent; HID; Incandescent |
| Photocontrol Sensor Location | Side |
| Dimensions | |
| Product Height (in) | 5 |
| Product Height (mm) | 139.7 |
| Product Width (in) | 1.5625 |
| Product Width (mm) | 39.7 |
| Product Depth (in) | 1.5625 |
| Product Depth (mm) | 39.7 |
| Wire Lead Length (in) | 6 |
| Wire Size Max | #18 AWG |
| Load Ratings | |
| Magnetic Ballast Range(s) | 8.3 A, 1000-2300 VA |
| Tungsten Range(s) | 15 A, 1800-4150 W |

Electrical Specifications

| | |
|------------------------|-----------------------|
| Input Voltage Range(s) | 120-277 VAC, 50/60 Hz |
|------------------------|-----------------------|

Packaging

| | |
|---------------------------------------|---------------------|
| Shipping Weight (lbs) | 0.451 |
| Unit Carton Dimensions (H x W x D) in | 5.75 x 3.5 x 3.5 in |

Environmental Specifications

| | |
|-------------------------|--------------|
| Temperature (operation) | -40°C...70°C |
| Usage Environments | Outdoor |

Standards and Certifications

| | |
|--|-----------------------------|
| UL Certification | UL |
| CSA Certification | cCSAus |
| Other Certifications and Compatibilities | NOM; Title 20; Ansi C136.10 |
| California Proposition 65 | None |
| RoHS Certification | X |

ACCESSORIES



22LG116
Light Guard Accessory for K4100 Series, K4200 Series
Thermal Photocontrols



K42-SW-A
Swivel Arm Accessory for EK4136S, K4100 Series Stem
Mount Photocontrols



6LV1352
Light Shield Accessory for EK4036S, EK4436SM, K4000
Series Button Photocontrols