

# Weather Proof Cover - Low-Profile Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, White

# Item WP7000W



# **PRODUCT DESCRIPTION**

Plastic In-Use Weatherproof Covers are easy to install and include a gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

## **FEATURES**

- ► 100% Paintable surface
- ► Complies with 2020 NEC Article 406.9 (B)(1) for wet locations and extra-duty applications
- ► CEC Article 26-702 Compliant
- ► UL Certified for Type 3R outdoor enclosures
- ► Meets requirements for cold impact testing: -60° F (-51° C)
- ► Heavy-duty UV stabilized polycarbonate cover, mounting base, and inserts
- ▶ 1/8" (3 mm) thick, neoprene gasket with slits for mounting screws
- ► Lockable hasp: All models accept up to 0.19" dia shank
- ► Impact rated: 12 lbf. impact test to ensure cover remains intact
- ► Reinforced hinge pin designed to exceed 40 lbf. hinge hang/stress test

### **APPLICATIONS**

Receptacle Protection

#### **TECHNICAL DATA**

General	
Model Number	WP7000W
Description	Low-Profile Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, White
UPC Code	078275149885
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	2
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	Yes

Dimensions	
Lockable Hasp Maximum Diameter (in)	0.19
Lockable Hasp Maximum Diameter (mm)	4.8
Product Dimensions (H x W x D) in	5.5 x 3.75 x 1.5 in
Expandable Depth Mm	54
Expandable Depth In	2 1/8
Accepted Cord Size Max	1x16 AWG
Вох Туре	Single

Material Specifications	
Color	Clear; White
Weatherproof Cover Material	UV Stabilized Plastic



Packaging	
Shipping Weight (lbs)	0.35
Product Weight (kg)	0.159
Unit Carton Dimensions (H x W x L) in	1.5 x 3.7 x 5.5 in
Product Weight (lbs)	0.35

Standards and Certifications		
UL Certification	cULus	
California Proposition 65	None	
RoHS Certification	γ	