

In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 5,10,15,30 Minute, With Hold, White, Mexico Sales Only

Item EI200WMX



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from five minutes to 30 minutes
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI200WMX
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 5,10,15,30 Minute, With Hold, White, Mexico Sales Only
UPC Code	078275095199
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Time Presets	5 min; 10 min; 15 min; 30 min
Setpoint Program Count	4
Operation Mode	Countdown
Countdown Time	30 min
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
Material Specifications	
Color	White

Load Ratings	
Resistive Heater	15 A, 1800 W
Tungsten (Incandescent) Range(s)	1000 W
Ballast Fluorescent	8 A, 1000 VA
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP
Electrical Specifications	
Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Environmental Specifications	
Temperature (operation)	32 - 104 °F / 0 - 40 °C
Packaging	
Shipping Weight (lbs)	0.351
Unit Carton Dimensions (H x W x D) in	6.131 x 2.131 x 3.001 in
Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	X