

In-Wall Timer

- Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, Light Almond

Item EI235LA



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from 15 minutes to 2 hours
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI235LA
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, Light Almond
UPC Code	078275111196
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Time Presets	15 min; 30 min; 45 min; 1 hr; 2 hrs
Setpoint Program Count	5
Operation Mode	Countdown
Countdown Time	2 hrs
Hold Mode Included	No
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
Material Specifications	
Color	Light Almond

Load Ratings

Resistive Heater	15 A, 1800 W
Tungsten (Incandescent) Range(s)	1000 W
Ballast Fluorescent	8 A, 1000 VA
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.4
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

Standards and Certifications

UL Certification	cULus
California Proposition 65	None