

In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 10,20,30,60 Minute, With Hold, Light Almond, Mexico Sales Only

Item EI210LAMX



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from 10 minutes to 1 hour
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI210LAMX
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 10,20,30,60 Minute, With Hold, Light Almond, Mexico Sales Only
UPC Code	078275100589
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Time Presets	10 min; 20 min; 30 min; 60 min
Setpoint Program Count	4
Operation Mode	Countdown
Countdown Time	60 min
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
Material Specifications	
Color	Light Almond

Load Ratings	
Resistive Heater	15 A, 1800 W
Tungsten (Incandescent) Range(s)	1000 W
Ballast Fluorescent	8 A, 1000 VA
Electronic Ballast LED	500 VA
Motor Load Ratings Ranges	1/4 HP
Electrical Specifications	
Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Environmental Specifications	
Temperature (operation)	32 - 104 °F / 0 - 40 °C
Packaging	
Shipping Weight (lbs)	0.4
Unit Carton Dimensions (H x W x D) in	2.251 x 2.881 x 4.751 in
Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	X