

Electronic Timer Control - 7-Day Electronic Time Switch Mechanism - Mechanism Only

Item P7103ME



PRODUCT DESCRIPTION

These digital time switches allow multiple ON/OFF cycles within a 24-hour time period for up to seven days.

FEATURES

- ▶ Turn equipment ON/OFF up to 8 times per day
- ▶ To-the-minute programming accuracy
- ▶ Dual-voltage input (3-wire)
- ▶ Timer override
- ▶ Select feature enables timers to be continuously in ON/OFF/AUTO mode
- ▶ 24-hour and 7-day models
- ▶ 3-year service life, replaceable lithium battery

APPLICATIONS

- ▶ Motor Control
- ▶ Pump Control

TECHNICAL DATA

| General                           |   |
|-----------------------------------|---|
| Model Number                      | P7103ME   |
| Description                       | 7-Day Electronic Time Switch Mechanism - Mechanism Only |
| UPC Code                          | 078275071582  |
| Brand                             | Intermatic  |
| Country of Origin (Intermatic)    | TAIWAN  |
| Warranty Period                   | 1-Year limited  |
| Control Specifications            |   |
| ON/OFF Operations                 | 8   |
| Operation Mode                    | 7 day   |
| Backup Type                       | Battery   |
| Battery Type                      | Lithium   |
| Backup Protection Time            | 3 Years   |
| Battery Service Type              | Replaceable   |
| Dimensions                        |   |
| Product Dimensions (H x W x D) in | 9.437 x 6.5 x 3.687 in                                  |
| Communication Method              |   |
| Has WiFi                          | No  |
| Load Ratings                      |   |
| Tungsten Range(s)                 | 12.5 A (1500 W), 120 VAC, 50/60 Hz                      |
| Resistive Load Ratings Ranges     | 20 A, 120/240 VAC, 50/60 Hz                             |
| Motor Load Ratings Ranges         | 1 1/2 HP @ 120 VAC, 50/60 Hz; 3 HP @ 240 VAC, 50/60 Hz  |



| Electrical Specifications |                   |
|---------------------------|-------------------|
| Input Voltage Range(s)    | 120 VAC, 50/60 Hz |
| Switch Type               | DPST              |

| Packaging                             |                    |
|---------------------------------------|--------------------|
| Shipping Weight (lbs)                 | 1.647              |
| Unit Carton Dimensions (H x W x L) in | 8.5 x 3.5 x 5.5 in |

| Standards and Certifications |        |
|------------------------------|--------|
| CSA Certification            | cCSAus |
| California Proposition 65    | DEHP   |
| RoHS Certification           | X      |