

Item Bundle - MultiWave® ECS System with 60 A Load Center, Expansion Module

Item PE25065RC



PRODUCT DESCRIPTION

This system includes the MultiWave Basic and an Expansion Module to control up to four valve actuators, two heaters, most name brand variable speed pumps and solar heating/cooling. The Remote Switch feature provides simple ON/OFF control of several components (i.e., spa heater, spa blower, spa lights) simultaneously with the flip of a single switch.

FEATURES

- Four breaker spaces
- Controls 5 circuits
- Controls 4 actuator ports (actuators not included), 2 for pool to spa valve rotation, 1 for water feature valve rotation, and 1 for solar applications
- Controls 2 heater circuits
- USB port for ease of upgrading firmware
- Load center dead front has two knockouts for switches and GFCIs
- Remote switch for simple ON/OFF control of several components at the same time

APPLICATIONS

- Heater Thermostat Control
- Motor Control
- Pump Control

TECHNICAL DATA

General	
Model Number	PE25065RC
Description	MultiWave® ECS System with 60 A Load Center, Expansion Module
UPC Code	078275145511
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	2-Year limited
Control Specifications	
Number Of Heaters Controlled	2
Mechanical Specifications	
Number of Breaker Knockouts	4
Enclosure Type	3R Beige metal
Dimensions	
Product Dimensions (H x W x D) in	16.875 x 10.875 x 4.75 in
Knockout Dimensions Bottom	(1) 1 1/8" diameter hole, (6) combination 1/2" - 3/4", (3) combination 3/4" - 1"
Knockout Dimensions Back	(1) combination 3/4" - 1
Knockout Dimensions Left	(2) combination 1/2" - 3/4"
Knockout Dimensions Right	(1) 1 3/4" x 2 3/4" for mounting switches or GFCI
Material Specifications	
Color	Beige



Load Ratings	
Load Center Ratings	60 A;60 A, 208 VAC, Single Phase
Motor Load Ratings Circuits 2 - 5	60 LRA @ 120 VAC, 50 Hz; 60 LRA @ 240 VAC, 50 Hz; 10 FLA @ 120 VAC, 50 Hz; 10 FLA @ 240 VAC, 50 Hz; 60 LRA @ 120 VAC, 60 Hz; 60 LRA @ 240 VAC, 60 Hz; 10 FLA @ 120 VAC, 60 Hz; 10 FLA @ 240 VAC, 60 Hz
Resistive Load Ratings Circuits 2 - 5	15 A, 120 VAC; 15 A, 240 VAC
Circuit 1 Resistive Display	20 A
Circuit 1 Motor Display	80 LRA @120/240 VAC; 17 FLA @120/240 VAC
Circuit 2 to 5 Resistive Display	15 A
Circuit 2 to 5 Motor Display	60 LRA @120/240 VAC; 10 FLA @120/240 VAC
Load Center Rating Display	60 A, 120/240 VAC or 120/208 VAC, Single Phase
Motor Load Ratings Ranges	80 LRA @ 120/240 VAC, 50/60 Hz; 17 FLA @ 120/240 VAC, 50/60 Hz
Electrical Specifications	
Number of Circuits	5
Number of Actuators Controlled	4
Number of Receptacle/Switch Knockouts	2
Packaging	
Shipping Weight (lbs)	25.1
Unit Carton Dimensions (H x W x L) in	18.125 x 9.75 x 16.625 in
Standards and Certifications	
CSA Certification	cCSAus
Other Certifications and Compatibilities	Title 20; Florida Energy Efficiency Code; Z-Wave
California Proposition 65	DEHP
RoHS Certification	X