

Displays - Display, BIT25

Item LCD-5S-1I

FEATURES

- ► Display for BIT25 Controller
- ► Fits standard opening for refrigerated case controllers



APPLICATIONS

- ► Ice Refrigeration Machine
- ► Reach-In Refrigeration Cooler



TECHNICAL DATA

General	
Model Number	LCD-5S-1I
Description	Display, BIT25
UPC Code	078275151581
Brand	LAE
Country of Origin (Intermatic)	ITALY
Warranty Period	5-Year limited

Control Specifications	
Mechanism Tyne	Flectrical

Defrost LED Indicator Red

Mechanical	Specifications		
------------	----------------	--	--

Enclosure Type IP55 Front
Has Finger-Safe Terminals Yes

29

Dimensions	
Product Dimensions (H x W x D) in	1.378 x 3.031 x 0.787 in
Panel Opening Height (in)	1 14

 Panel Opening Height (mm)
 29

 Panel Opening Width (in)
 2.80

 Panel Opening Width (mm)
 71

 Panel Opening Width (mm)
 71

 Cut-Out Width (ln)
 2.80

 Cut-Out Width (mm)
 71

 Cut-Out Height (in)
 1.14

Electrical Specifications

Cut-Out Height (mm)

Wiring Option Plug Terminal

Technical specifications and other information are subject to change without notice. Images can vary from original.

RoHS Certification



Display and Format	
Clock Display Types	LED
Packaging	
Shipping Weight (lbs)	0.065
Product Weight (kg)	0.03
Unit Carton Dimensions (H x W x L) in	2.5 x 3.2 x 3.6 in
Product Weight (lbs)	0.065
Operating Specifications	
Expected Lifetime (Years)	5
Environmental Specifications	
Quartz Temperature Min (°C)	-10
Quartz Temperature Min (°F)	14
Quartz Temperature Max (°F)	122
Storage Temperature Min (°F)	14
Quartz Temperature Max (°C)	50
Storage Temperature Max (°F)	122
Storage Temperature Min (°C)	-10
Storage Temperature Max (°C)	50
Temperature (operation)	14 °F to 122 °F / (-10 °C to 50 °C)
Standards and Certifications	
California Proposition 65	None