

Photocontrol - Button Thermal Photocontrol, 480 V

Item K4035



PRODUCT DESCRIPTION

These photocontrols install within lighting fixtures, post lamps, or in-wall boxes to provide dusk-to-dawn ON/OFF control of outdoor lighting.

FEATURES

- ► Mechanical bimetal switch with Cadmium Sulfide photocell
- ► Compact size fits into standard outlet box, post lamp, wall pack and other lighting fixtures
- ► Delay feature prevents unwanted OFF switching
- ▶ 3/8"-18 NPSM, 3/4" long stem with locking nut and washer gasket

APPLICATIONS

► Outdoor Lighting Control

TECHNICAL DATA

PAZO

| General | |
|--------------------------------|------------------------------------|
| Model Number | K4035 |
| Description | Button Thermal Photocontrol, 480 V |
| UPC Code | 078275530041 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 2-Year limited |

| Control Specifications | |
|------------------------------|--------------------------------|
| Sensor Time Delay | 30 sec to 90 sec |
| Photocell Type | Cadmium Sulfide |
| Photo Control Switch Type | Mechanical Bimetal |
| Fail Mode | ON |
| Activation On | 1 to 5 fc |
| Activation Off | 3 to 15 fc |
| Photocontrol Type | Thermal |
| Application Compatibilities | HID; Fluorescent; Incandescent |
| Photocontrol Style | Button |
| Photocontrol Sensor Location | Front |

| Dimensions | |
|-----------------------|---------|
| Product Height (in) | 1 13/16 |
| Product Height (mm) | 46 |
| Product Width (in) | 15/16 |
| Product Width (mm) | 23.8 |
| Product Depth (in) | 13/16 |
| Product Depth (mm) | 20.6 |
| Wire Lead Length (in) | 9 |
| Wire Lead Length (mm) | 228.6 |



Wire Size Max #18 AWG

| Material Specifications | | |
|---------------------------------------|--------------------|--|
| Cover Color | Gray | |
| Housing Material | Polycarbonate | |
| | | |
| Load Ratings | | |
| Magnetic Ballast Range(s) | 8.3 A, 4000 VA | |
| Tungsten Range(s) | 15 A, 7200 W | |
| | | |
| Electrical Specifications | | |
| Wiring Option | Wire leads | |
| Input Voltage Range(s) | 480 VAC, 50/60 Hz | |
| | | |
| Packaging | | |
| Shipping Weight (lbs) | 0.25 | |
| Unit Carton Dimensions (H x W x D) in | 4.88 x 1.75 x 3 in | |
| | | |
| Operating Specifications | | |
| Expected Lifetime (Years) | 5 | |

| ating openitorions | |
|--------------------------------|------|
| Expected Lifetime (Years) | 5 |
| Expected Lifetime (Operations) | 3650 |

| Environmental Specifications | | |
|------------------------------|-----------|--|
| Temperature (operation) | -40°C70°C | |
| Usage Environments | Outdoor | |

| Standards and Certifications | |
|--|----------|
| Other Certifications and Compatibilities | Title 20 |
| California Proposition 65 | DEHP |



ACCESSORIES



6LV1352 Light Shield Accessory for EK4036S, EK4436SM, K4000 Wall Plate Kit for EK4036S, K4000 Series Button Series Button Photocontrols



K43-WP-KIT Photocontrols



LGLBL Lens Sticker Accessory for EK4000 & K4000 Series Photocontrols