

Photocontrol - Button Thermal Photocontrol, 208-277 V, Mexico Sales Only

Item K4023CMX



PRODUCT DESCRIPTION

These photocontrols install within lighting fixtures, post lamps, or in-wall boxes to provide dusk-to-dawn ON/OFF control of outdoor lighting.

FEATURES

- ▶ Mechanical bimetal switch with Cadmium Sulfide photocell
- ▶ Compact size fits into standard outlet box, post lamp, wall pack and other lighting fixtures
- ▶ Delay feature prevents unwanted OFF switching
- ▶ 3/8"-18 NPSM, 3/4" long stem with locking nut and washer gasket

APPLICATIONS

- ▶ Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	K4023CMX
Description	Button Thermal Photocontrol, 208-277 V, Mexico Sales Only
UPC Code	078275029576
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited

Control Specifications	
Sensor Time Delay	30 sec to 90 sec
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Activation On	1 to 5 fc
Activation Off	3 to 15 fc
Photocontrol Type	Thermal
Application Compatibilities	HID; Fluorescent; Incandescent
Photocontrol Style	Button
Photocontrol Sensor Location	Front

Dimensions	
Product Height (in)	1.8125
Product Height (mm)	46
Product Width (in)	0.938
Product Width (mm)	23.8
Product Depth (in)	0.813
Product Depth (mm)	20.6
Wire Lead Length (in)	9
Wire Lead Length (mm)	228.6

Wire Size Max #18 AWG

Material Specifications

Cover Color Gray
Housing Material Polycarbonate

Load Ratings

Magnetic Ballast Range(s) 8.3 A, 1700-2300 VA
Tungsten Range(s) 15 A, 3100-4150 W

Electrical Specifications

Wiring Option Wire leads
Input Voltage Range(s) 208-277 VAC, 50/60 Hz

Packaging

Shipping Weight (lbs) 0.25
Unit Carton Dimensions (H x W x D) in 4.88 x 1.75 x 3 in

Operating Specifications

Expected Lifetime (Years) 5
Expected Lifetime (Operations) 3650

Environmental Specifications

Temperature (operation) -40°C..70°C
Usage Environments Outdoor

Standards and Certifications

UL Certification UL
CSA Certification cCSAus
Other Certifications and Compatibilities Title 20; NOM
California Proposition 65 None
RoHS Certification X

ACCESSORIES



LGLBL
Lens Sticker Accessory for EK4000 & K4000 Series
Photocontrols



6LV1352
Light Shield Accessory for EK4036S, EK4436SM, K4000
Series Button Photocontrols



K43-WP-KIT
Wall Plate Kit for EK4036S, K4000 Series Button
Photocontrols