

## Irrigation Timer - Sprinkler/Irrigation Time Switch with 14-Day Skipper

Item R8806P101C



### PRODUCT DESCRIPTION

These irrigation timers are designed to permit one to 44 "ON" operations every 24 hours and provide watering increments down to 12 minutes or up to 20 hours and 45 minutes to ensure proper watering increments. These models also allow for biweekly scheduling with the convenient 14-day skipper for maximum water conservation and odd/even day compliance.

### FEATURES

- ▶ Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ▶ 14-Day skipper enables irrigation to be omitted on selected day(s)
- ▶ Allows for alternate-day scheduling
- ▶ ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ▶ Type 3R plastic indoor/outdoor enclosure

### APPLICATIONS

- ▶ Agriculture Feeders
- ▶ Greenhouse Misting Control
- ▶ Landscape Water Control

### TECHNICAL DATA

#### General

Model Number	R8806P101C
Description	Sprinkler/Irrigation Time Switch with 14-Day Skipper
UPC Code	078275005105
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	12 min
Maximum ON/OFF Times	20 hours, 45 minutes
Maximum ON/OFF Operations	44
Tripper Actuating Time	12 min
Mechanism Type	Analog/Mechanical

#### Mechanical Specifications

Enclosure Type	Indoor/outdoor type 3R plastic
Number of Trippers Included	12

#### Dimensions

Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

#### Material Specifications

Color	Gray
-------	------

**Load Ratings**

Clock Motor Voltage	208/277 VAC, 60 Hz
Motor Load Ratings Ranges	3 HP @ 240 VAC, 60 Hz

**Electrical Specifications**

Input Voltage Range(s)	240 VAC, 60 Hz
Switch Type	DPST
Load Voltage	240 VAC, 60 Hz
Amps Per Pole	30 A
HP	3

**Packaging**

Shipping Weight (lbs)	2.644
Unit Carton Dimensions (H x W x L) in	4.25 x 7.31 x 11.75 in

**Environmental Specifications**

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

**Standards and Certifications**

CSA Certification	cCSAus
California Proposition 65	None
RoHS Certification	X

**ACCESSORIES**



**156T1950A**  
Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series



**133T700A**  
Micro Switch for T8800 and R8800 Series



**156T1954A**  
14 Skipper Pins for R8800, and T8800 Series



**107T73**  
Replacement Day Wheel Pins for T8800 and R8800 Series



**107T119**  
Tripper (Silver) for T8800 and R8800 Series (Day Skipper)



**124T2097**  
Insulator for R8806P101C, T8805P101C, T8845PV



**133T1115A**  
Toggle Switch for T8800 and R8800 Series



**143T138**  
Relay Kit, DPST, 3 HP, 240 VAC (S)



**156T1950AD12**  
12 Bags of 156T1950A Trippers for T1900, T2000, C8800, R8800, and T8800 Series

**WG730-14D**  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**WG730-14DMX**  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**WG733-14D**  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**WG733-14DMX**  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**156T2978A**  
Package Accessory Trippers



**6T1339**  
Cover, Gray plastic



**WG736-14D**  
480 V, 60 Hz Motor for T1900, T8800, R8800 Series